



Badger Quality in Sparkling Chrome

Introducing Badger's beautiful line of custom chrome fire extinguishers.

Now the best Badger ABC Multipurpose and Halotron-1™ Stored Pressure extinguishers are available in high quality chrome finish for custom designer, marine and automotive applications.

These extinguishers bring safety and compliance with a touch of class to special promotions and to customizing automobiles and motorcycles, boats, high-end business offices and other applications where appearance is a priority.



B5M

B250M

BADGERExtra - Chrome ABC
Compliance for custom applications

Chrome Halotron-1™ Clean Agent



BADGERExtra - Chrome Halotron-1™
Clean agent in a good-looking package

Chrome ABC Multipurpose

Badger chrome extinguishers feature:

- 2.5 and 5 pound models
- High quality coated chrome plated cylinders
- Laser welded cylinders
- Stainless steel handles and levers
- Stainless steel hose band and nozzle retainer
- UL Listed & U.S. Coast Guard Approved
- 12 year periodic hydrostatic test interval
- Six year product warranty
- Plated brass valve and steel siphon tube
- Large loop stainless steel pull pins with tether
- Multipurpose Dry Chemical contains 90% M.A.P.
- Halotron-1 is an environmentally acceptable Halon-1211 alternative

Technical Data: **BADGER**Extra - Custom Chrome Fire Extinguisher Models

MODEL	B250M Chrome			B5M Chrome			2.5 HB-2 Chrome			5 HB-2 Chrome		
PART NUMBER	24805			24808			24812			24814		
CAPACITY (lb.)	2.5			5			2.5			5		
CAPACITY (kg)	1.1			2.3			1.1			2.3		
UL FIRE RATING	1-A:10-B:C			3-A:40-B:C			2-B:C			5-B:C		
AGENT TYPE	ABC			ABC			Halotron-1			Halotron-1		
CYLINDER MATERIAL	Chrome Plated Steel			Chrome Plated Steel			Chrome Plated Steel			Chrome Plated Steel		
VALVE MATERIAL	Plated Brass			Plated Brass			Plated Brass			Plated Brass		
HANDLE/LEVER MATERIAL	Stainless Steel			Stainless Steel			Stainless Steel			Stainless Steel		
EXPELLANT	Nitrogen			Nitrogen			Argon			Argon		
TEMPERATURE RANGE (F)	-40	to	120	-40	to	120	-40	to	120	-40	to	120
TEMPERATURE RANGE (C)	-40.0	to	48.9	-40.0	to	48.9	-40.0	to	48.9	-40.0	to	48.9
AGENT FLOW RATE (lb/sec)	0.31			0.39			0.63			0.56		
AGENT FLOW RATE (kg/sec)	0.1			0.2			0.3			0.3		
NOM. DISCHARGE TIME (sec)	9			14			9			9		
DISCHARGE RANGE (ft.)	10.0	to	15.0	12.0	to	18.0	6.0	to	10.0	9.0	to	15.0
DISCHARGE RANGE (m)	3.0	to	4.6	3.7	to	5.5	1.8	to	3.0	2.7	to	4.6
UNIT HEIGHT (in.)	14.88			15.25			14.88			15.25		
UNIT HEIGHT (cm)	37.8			38.7			37.8			38.7		
UNIT WIDTH (in.)	5.5			7.5			6.13			6.13		
UNIT WIDTH (cm)	14.0			19.1			15.6			15.6		
UNIT DEPTH (in.)	3			4.25			3			4.25		
UNIT DEPTH (cm)	7.6			10.8			7.6			10.8		
SHIPPING WEIGHT (lb)	6.25			10.4			6.85			10.6		
SHIPPING WEIGHT (kg)	2.8			4.7			3.1			4.8		
USCG APPROVAL				Type A Size-II								
	Type B:C Size-I			Type B:C Size-I						Type BC Size-1		
BRACKET	MB-250B			MB-5B			MB-250B			B5M-B		
	Included			Optional			Included			Optional		

Distributed by:



Badger Fire Protection
 4251 Seminole Trail • Charlottesville, VA 22911
 Tel 800 446 3857 or 434 973 4361
 Fax 800 248 7809 or 434 973 1589
www.badgerfire.com

 **A Kidde Company**

BFPN 0011